


INQUIRY FORM

for the purpose of quotations and production

Contact details


Company		Email	
Contact person		Phone	
Address			



PROFILE DRESSER

- > Copy dressing of high-precision profiles in grinding wheels
- > Dressing the following types of grinding wheels: corundum, white corundum, silicon carbide, sintered corundum

Radius: 0,125 – 0,500 mm




Angle: 30°–90°

CVD

MKD

Natural stone*




Quantity

Diaform



Cylindrical



Holder length 35 mm

Ø (D) in mm

45 mm


55 mm

Length (L) in mm

MK0


MK1

MK1 kurz




Radius	Angle
<input type="checkbox"/> 0,125 mm	<input type="checkbox"/> 30°
<input type="checkbox"/> 0,250 mm	<input type="checkbox"/> 40°
<input type="checkbox"/> 0,500 mm	<input type="checkbox"/> 60°
<input type="checkbox"/> Other:	<input type="checkbox"/> Other:

„Schaudt“



Drill hole

„Fortuna“



Drilling Yes

No

Other

Carat size* 0,25 0,33 0,5 0,75 1,0 1,25 1,5 1,75 2,0

*Please fill in carat size only for natural stone.

Abrasive grit	<input type="checkbox"/> Corundum	<input type="checkbox"/> Silicon carbide	<input type="checkbox"/> Other	Ø in mm	Width in mm
Profile	<input type="checkbox"/> Yes	<input type="checkbox"/> No	Graining	Cooling <input type="checkbox"/> Yes <input type="checkbox"/> No	<input type="checkbox"/> Emulsion <input type="checkbox"/> Oil
Description of the dressing procedure/process					

You have not found the right tool for your application? Please do not hesitate to contact us.